

GEN - 2 Remote Programing With Control Panel

REMOTE CONTROLS

To pair a remote control to the unit, press the canopy light on/off button and the Lock/Unlock buttons down together on the front of the control panel for 1 - 2 seconds and let go. The Status light will Blink Red letting you know you entered the programing mode. Now press any button on the remote control and let go. Wait for the Red Status light to go out and then try the remote. Do the same thing to pair multiple remote controls. You can have a maximum of 5 remote controls programed at one time. If you need to clear the board for any reason hold down the Canopy Light and the Lock/Unlock button for 10 seconds. This will erase all remote controls and phones paired to the control panel.



LOCKING THE CONTROL PANEL:

Hold the lock/unlock button until the ready and status light start blinking (About 10 seconds) to lock the control panel. Hold it again until the ready and status light stop blinking to unlock the control panel. When the control panel is locked the 3 lights will blink for a set amount of time and then stop. Remote controls will not work when the control panel is locked. Bluetooth will still work.



If your neighbors have a Lift Tech Marine unit, make sure they are not using their lift while you are programming.

Bluetooth:

To pair a phone with Bluetooth press the UP and DN key at the same time and then release. This will activate the Bluetooth pairing sequence. See the IOS or Android instructions to finish pairing the phone to the control panel. Or visit us online at www. lifttechmarine.com under manuals and then Bluetooth setup.

www.lifttechmarine.com 866-319-8877

